



(FRAME ONLY)





3

4

## PJUUR®

imagine invisible

PJ-AERO M-R-ST


## PJ-AERO-R-COLLAR Ø125 (order separately)

TO BE USED WITH COVER:


PJ-AERO-M-R-COVER C

1

2



Optional collar (order separately)




6

5








Check and Clean the Air Ventil regularly or replace with: PJ-AERO-R-FELT AIR VENTIL



PJUUR® Brielmolenstraat 51 9160 Lokeren (B) www.pjuur.com Tel.+32 9 337 01 48 info@pjuur.com





All models and designs are the intellectual property of PJUUR®. All models and designs are registered by copyright, (utility) model protection and/ or patent under the Benelux and European Law. ©V3Lighting bv / PJUUR® v4-18/03/2021

## GENERAL CONDITIONS / PRODUCT LIABILITY / WARRANTY

- The products should be checked, installed, build-in, connected and tested by a certified installer.
- The products should be installed in accordance to the local regulations of buildings and electric installations.
- The products should always be installed or replaced with the necessary care.
- Do not drop, throw, ... the frames and products. Smartphones and tablets are also not designed to drop them or to be handled
- carelessly. The products may seem to be fragile, as they are made from reinforced plaster, but in case of negligence, damage is a result. - Before installing: Check the frames and products on any damage and/ or inconsistencies. Damaged products may not be installed.
- Please read all instructions prior to assembly. Follow it step by step.
- Do not use machines and/or electric hand tools.
- Use a manual screwdriver: tighten the screws carefully.
- PJUUR takes no responsibility on the final installation of the frames and/or faulty installed products.
- Turn off the power supply before installation or maintenance of the frames, the products or the installed equipment.
- Misuse of, or changes to the products shall nullify any guarantee.
- Keep children away from the products.
- Never cover the products with e.g. insulating material.
- The information, specifications and details of the products in this document are subject to change without notice; the manufacturer is free to change the design, specifications and instructions for installation.
- PJUUR assumes no responsibility or liability for any errors, inaccuracies that may appear in this manual.
- Leave a copy of this document with person responsible for maintenance.
- This document is part of the general selling conditions of PJUUR. The customer is supposed to know our general selling conditions.
- In case of doubt contact the manufacturer: info@pjuur.com.

## READ BEFORE PLASTERING

- Finish the HW-frames like normal drywall systems.
- Finish the ST-frames like regular plaster finishing.
- Use glass fiber mesh tape on the joints.
- Only install the frames when the construction is completely windproof!
- Do not use excessive water or do not moisture the frames excessively.
- Avoid (yellow) StucPrimer on the visible part of the frames.
- The front-side of frames can be used as reference surface when plastering. Keep visible contour / edges clean at all time!
- In case of uneven ceilings or walls or when thick layer of plaster must be used:
  - First plaster the wall or ceiling and keeping the frame untouched.
  - Let it dry.
  - Check the position of the frame and fine-tune if necessary.
  - Plaster up to the border of the frame and finish.

